






















Snaga u brojevima













Fleksibilnost i prilagodljivost Hiacea čine ga pravim višenamenskim "fizikalcem".

Sveobuhvatan asortiman modela daje vam potpunu slobodu izbora, omogućavajući vam da odaberete baš onakav kombi kakav vam treba.

Modeli sa dugom šasijom mogu prevesti osam ljudi i njihov prtljag, ali kada je naglasak na nosivosti, Hiace može biti u verziji sa jednim redom sedišta. Mnoštvo konfiguracija Hiacea je prikazano ispod.

Modeli	Kratak furgon	Produženi furgon	Kratak Kombi-bus	Produženi Kombi-bus
				
Oprema Base				
Oprema Comfort				
Oprema Style				
Oprema City				
4 vrata (klizna vrata sa jedne strane)				
5 vrata (klizna vrata sa obe strane)	 *	 *		
Zadnja vrata koja se otvaraju na gore				
Zadnja vrata koja se otvaraju u stranu				

* Dostupno za modele sa pogonom na sva četiri točka.

Modeli	Kratak furgon	Produženi furgon	Kratak Kombi-bus	Produženi Kombi-bus
Tri sedišta				
Osam sedišta				
Tovarna zapremina (m3) sa 3 osobe	 5.5	 6.5		
Tovarna zapremina (m3) sa 8 osoba			 1.3	 2.3

Pravi Hiace za vaše potrebe

KRATAK FURGON				KRATAK KOMBI-BUS
Model	1	2	3	4
Pogon	2WD	2WD	4WD	2WD
Sedišta	3	3	3	8
Vrata	4	4	5	4
Motor	2.5 D-4D (70 kW)	2.5 D-4D (86 kW)	2.5 D-4D (86 kW)	2.5 D-4D (86 kW)
Menjač	5 M/T	5 M/T	5 M/T	5 M/T
Nivo opreme	Base i Comfort	Comfort	Comfort	Style i City
Ukupna dužina (mm)	4795	4795	4795	4795
Ukupna širina (mm)	1800	1800	1800	1800
Ukupna visina (mm)	2000	2000	1995	1985
Međuosovinsko rastojanje (mm)	2985	2985	2985	2985
Razmak prednjih točkova (mm)	1560	1560	1550	1560
Razmak zadnjih točkova (mm)	1540	1540	1540	1540
Klirens (mm)	195	195	190	195
Min. radijus okretanja (m)	5.5	5.5	6.3	5.5
Dužina prostora za teret (mm)	2335	2335	2335	545
Širina prostora za teret (mm)	1650	1650	1650	1650
Visina prostora za teret (mm)	1420	1420	1420	1410
Masa praznog vozila (kg)	1665–1830	1665–1830	1800–1965	1775–1875
Ukupna masa vozila (kg)	2800	2800	2900	2600
Maksimalna nosivost (kg)	1135–970	1135–970	1110–935	825–725
Tovarna zapremina (m ³)	5.5	5.5	5.5	8PI+1.3
Težina prikolice sa kočnicom (kg)	2000	2000	2000	2000

PRODUŽENI FURGON				PRODUŽENI KOMBI-BUS
Model	9	10	13	15
Pogon	2WD	2WD	4WD	2WD
Sedišta	3	3	3	8
Vrata	4	4	5	4
Motor	2.5 D-4D (70 kW)	2.5 D-4D (86 kW)	2.5 D-4D (86 kW)	2.5 D-4D (86 kW)
Menjač	5 M/T	5 M/T	5 M/T	5 M/T
Nivo opreme	Base i Comfort	Comfort	Comfort	Style
Ukupna dužina (mm)	5240	5240	5240	5240
Ukupna širina (mm)	1800	1800	1800	1800
Ukupna visina (mm)	1995	1995	1990	1980
Međuosovinsko rastojanje (mm)	3430	3430	3430	3430
Razmak prednjih točkova (mm)	1560	1560	1550	1560
Razmak zadnjih točkova (mm)	1540	1540	1540	1540
Klirens (mm)	205	205	200	195
Min. radijus okretanja (m)	6.2	6.2	7.0	6.2
Dužina prostora za teret (mm)	2780	2780	2780	990
Širina prostora za teret (mm)	1650	1650	1650	1650
Visina prostora za teret (mm)	1420	1420	1420	1420
Masa praznog vozila (kg)	1735–1900	1735–1900	1875–2045	1845–1945
Ukupna masa vozila (kg)	3000	3000	3000	2650
Maksimalna nosivost (kg)	1265–1100	1210–1100	1125–955	805–705
Tovarna zapremina (m ³)	6.5	6.5	6.5	8PI+2.3
Težina prikolice sa kočnicom (kg)	2000	2000	2000	2000

Specifikacije

POTROŠNJA I ZAŠTITA OKOLINE

Potrošnja goriva (1999/100/EC)	2.5 litara D-4D 2KD-HI (2WD)	2.5 litara D-4D 2KD-LO (2WD)	2.5 litara D-4D 2KD-HI (4WD)
Kombinovana vožnja (litara/100 km)	8.5	8.5	9.3
Vožnja van grada (litara/100 km)	7.1	7.1	8
Gradska vožnja (litara/100 km)	10.8	10.8	11.6
Preporučena vrsta goriva	dizel	dizel	dizel
Zapremina rezervoara za gorivo (litara)	75	75	75
Ugljen dioksid CO₂			
Kombinovana vožnja (g/km)	224	224	246
Vožnja van grada (g/km)	189	189	212
Gradska vožnja (g/km)	283	283	304
Emisije izduvnih gasova (EU direktiva 70/220-1999/102 (Stage 3)/EC)			
Ugljen monoksid, CO (g/km)	0.08	0.13	0.08
Ugljovodonici, HC (g/km)	–	–	–
Oksidi azota, NO _x (g/km)	0.31	0.32	0.31
Čestice, PM (g/km)	0.04	0.03	0.04
Ugljovodonici, HC i oksidi azota, NO _x (g/km)	0.32	0.34	0.32
Buka (u vožnji) (direktiva EU 1999/101/EC)			
Buka dB(A)	72.8	73.1	72.8

MOTOR

	Dizel	Dizel
Kod motora	2.5 litara D-4D 2KD-HI	2.5 litara D-4D 2KD-LO
Broj cilindara	4 u liniji	4 u liniji
Mehanizam ventila	16-ventila DOHC pogon remenom i zupčanicima	16-ventila DOHC pogon remenom i zupčanicima
Sistem ubrizgavanja goriva	Direktno ubrizgavanje sa common rail sistemom	Direktno ubrizg. sa common rail sistemom
Zapremina (ccm)	2494	2494
Promer i hod (mm)	92.0 x 93.8	92.0 x 93.8
Stepen kompresije	17.4:1	17.4:1
Maksimalna snaga (kW/o/min)	86 (117 DIN KS)/3600	70 (95 DIN KS)/3600
Maksimalni obrtni momenat (Nm/o/min)	294/1600–2400	230/1400–2600

PERFORMANSE

	2.5 litara D-4D 2KD-HI (5 M/T 2WD)	2.5 litara D-4D 2KD-LO (5 M/T 2WD)	2.5 litara D-4D 2KD-HI (5 M/T 4WD)
Maksimalna brzina (km/h)	152	147	151
0–100 km/h (sek)	18.6	22.4	19.7
0–400 m (sek)	20.7	21.9	21.1
Koeficijent otpora vazduha (CD)	0.36	0.36	0.36

OGIBLJENJE

Prednje	Dvostruka viljuška, torziona greda sa stabilizatorom
Zadnje	Nezavisno oslanjanje, opruga

KOČNICE

Prednje	Ventilisani diskovi
Zadnje	Doboš