



TOYOTA



PROACE MAX NADOGRADNJE

TEHNIČKE KARAKTERISTIKE

BOJE - PROACE MAX NADOGRADNJE



BIJELA ICE WHITE (EPR)
SOLID



SREBRNA MISTY GRAY (EAK)
SOLID



ANTHRACITE (EAB)
SOLID



SIVA IRON GREY (EZW)
METALIK



CRNA OPAL (EEA)
METALIK



**SREBRNA SILVER SHADOW
(KCA)**
METALIK

NAPLATCI - PROACE MAX NADOGRADNJE



**16" Čelični naplatci s pokrovima
kotača**

Dimenzija guma - 215/75/R16 C

TEHNIČKE KARAKTERISTIKE – PROACE MAX NADOGRADNJE

Performanse			ŠASIJA	ŠASIJA CREW	SANDUK	SANDUK CREW	KIPER
Motor	Broj cilindara, raspored		4 cilindra, redni	4 cilindra, redni	4 cilindra, redni	4 cilindra, redni	4 cilindra, redni
	Obujam	Cm ³	2184	2184	2184	2184	2184
	Maksimalna snaga	Kw/K S	103/140 -132/180	103/140 -132/180	103/140 -132/180	103/140 -132/180	103/140 -132/180
	Okretni moment	Nm	350 - 450	350 - 4500	350 - 450	350 - 450	350 - 450
Prijenos	Vrsta pogona		Prednji	Prednji	Prednji	Prednji	Prednji
	Tip mjenjača		M/T6 – A/T8	M/T6 – A/T8	M/T6 – A/T8	M/T6 – A/T8	M/T6 – A/T8
	Pogon						
Emisije	Euro Norma		EURO 6 E	EURO 6 E	EURO 6 E	EURO 6 E	EURO 6 E
	Rezervoar za gorivo	l	90	90	90	90	90
Kočnice	Kočnice prednje		Disk	Disk	Disk	Disk	Disk
	Kočnice stražnje		Disk	Disk	Disk	Disk	Disk
Pogon	Vrsta pogona		Prednji	Prednji	Prednji	Prednji	Prednji
Ovjes	Prednji		Neovisni McPherson	Neovisni McPherson	Neovisni McPherson	Neovisni McPherson	Neovisni McPherson
	Stražnji		Kruta osovina s lisnatim oprugama	Kruta osovina s lisnatim oprugama	Kruta osovina s lisnatim oprugama	Kruta osovina s lisnatim oprugama	Kruta osovina s lisnatim oprugama

Performanse		ŠASIJA L3	ŠASIJA L4	ŠASIJA CREW L3	ŠASIJA CREW L4	SANDUK L3	SANDUK L4	SANDUK CREW L3	SANDUK CREW L4	KIPER L3	KIPER L4	
Dimenzije	Ukupna dužina	mm	5943	6308	5943	6308	6328	6693	6228	6678	6170	6210
	Ukupna širina	mm	2050		2050		2100		2100		2100	
	Ukupna visina	mm	2254		2254		2376		2376		2376	
	Međuosovinski razmak	mm	4035		4035		4035		4035		4035	
	Prednji prevjes	mm	948		948		948		948		948	
	Stražnji prevjes	mm	960	1325	960	1325	948-1345	948-1710	948-1245	948-1695	948-1187	
	Duljina platforme	mm	-		-		3895	4260	2950	3400	3660	2860
	Širina platforme	mm	-		-		2100		2100		2100	
	Visina platforme	mm	-		-		400		400		400	
	Najveća došuštena masa	kg	3500		3500		3500		3500		3500	
	Ukupna dopuštena masa skupa vozila	kg	6500		6500		6500		6500		6500	
	Masa vozila u voznom stanju min/max	kg	1920-2102		2115-2315		2140-2347		2285-2494		2445-2785	
	Opterećenje prednje osovine	kg	2100		2100		2100		2100		2100	
	Opterećenje stražnje osovine	mm	2400		2400		2400		2400		2400	
	Širina prednjih kotala	mm	1810		1810		1810		1810		1810	
Širina stražnjih kotača	mm	1790		1790		1790		1790		1790		